



## BATH + LIGHT


### PRIDE 20W

PRIDE WEATHER PROOF FITTING

#### Indoor Luminaire

#### Product Code:

LPRD01X020XC / LPRD01X020XN / LPRD01X020XW  
20W - 2000lm - 6500K - CRI>80 Ra - Beam Angle 120°



### Technical Specifications


Operating Temperature	-10°C to 40°C
Rated Input Voltage & Frequency	230 VAC, 50Hz
Rated Input Wattage	20W ± 10%
Rated Input Current	0.085 Amp (Nominal)
Power Factor	≥0.9
ATHD	<10%
Rated Luminous Flux	2000 lm / 1900 lm / 1800 lm (tolerance as per BIS)
Rated Luminaire Efficacy	100 lm/W / 95 lm/W / 90 lm/W (tolerance as per BIS)
Correlated Color Temperature (CCT)	6500 K / 4000 K / 3000 K (tolerance as per ANSI)
Color Rendering Index (CRI)	>80 Ra
Beam Angle	120° (within the permissible limits)
Driver Efficiency	≥85%
LED Life Span	>50000 Hrs (Ta=25°C @L70)
Housing	PC. Housing
Lens / Reflector	PC. Diffuser
Mounting	Surface Mount

### Protections

Over Voltage Protection	Withstand upto 440V/AC for 4 Hrs.
Surge Protection	±4.0KV
Protection Class	Class II
Ingress Protection (IP Rating)	IP65
Impact Protection (IK Rating)	IK02
Short Circuit Protection	Provided
Open Circuit Protection (No Load)	Provided
Reverse Polarity Protection	Provided

All technical data is subject to industry-standard tolerances.

Light Distribution




UGR Table

ceiling/cavity		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
walls		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
working plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions	Viewed crosswise						Viewed endwise				
x = 2H y = 2H	2H	19.2	20.7	19.5	21.0	21.3	20.6	22.2	21.0	22.5	22.8
	3H	20.6	22.0	20.9	22.3	22.6	22.8	24.3	23.2	24.6	24.9
	4H	21.1	22.5	21.5	22.8	23.1	24.0	25.4	24.4	25.7	26.0
	6H	21.5	22.7	21.9	23.1	23.5	25.2	26.5	25.6	26.9	27.2
	8H	21.6	22.8	22.0	23.2	23.6	25.9	27.1	26.3	27.5	27.9
	12H	21.6	22.8	22.0	23.2	23.6	26.6	27.8	27.1	28.2	28.6
4H	2H	20.2	21.5	20.6	21.9	22.2	21.2	22.6	21.6	22.9	23.3
	3H	21.8	23.0	22.2	23.4	23.8	23.7	24.9	24.1	25.3	25.7
	4H	22.5	23.6	22.9	24.0	24.4	25.0	26.1	25.5	26.5	27.0
	6H	23.0	24.0	23.5	24.4	24.9	26.5	27.5	26.9	27.9	28.4
	8H	23.2	24.1	23.6	24.5	25.0	27.3	28.2	27.7	28.6	29.1
	12H	23.3	24.1	23.8	24.6	25.1	28.1	29.0	28.6	29.5	30.0
8H	4H	23.3	24.2	23.8	24.7	25.1	25.4	26.3	25.9	26.8	27.2
	6H	24.1	24.9	24.6	25.4	25.9	27.1	27.9	27.6	28.4	28.9
	8H	24.4	25.1	24.9	25.6	26.2	28.1	28.8	28.6	29.3	29.8
	12H	24.6	25.3	25.2	25.8	26.3	29.2	29.8	29.8	30.4	30.9
12H	4H	23.5	24.4	24.0	24.8	25.3	25.4	26.3	25.9	26.7	27.2
	6H	24.5	25.2	25.0	25.7	26.3	27.2	27.9	27.7	28.4	29.0
	8H	25.0	25.6	25.5	26.1	26.7	28.3	28.9	28.9	29.4	30.0
Variations with the observer position at spacings(CIE Pub.117) :											
S = 1.0H	+ 0.1 / - 0.1						+ 0.1 / - 0.1				
1.5H	+ 0.2 / - 0.3						+ 0.2 / - 0.3				
2.0H	+ 0.1 / - 0.4						+ 0.2 / - 0.4				

With our continuous efforts to upgrade the technology/product, all product specifications and data are subject to change without prior notice. We always try to maintain the accuracy of our product images, but due to different viewing conditions, the colors may vary. Images are only for indicative purpose.

## Product Dimensions (L x W x H)

590 X 86 X 67 mm



## Applications

Residences, Offices, Small Retail Shops, Hotels, Coffee Shops, Restaurants, Hospitals, area lighting and for other indoor applications.