

OPS-WHT-15951

SPECIFICATION DATA SHEET

PRODUCT DETAILS

TRODUCT BETALES								
Manufacturer :	Jaquar	Type: Wall hung WC (water closet)						
Range	Opal	Flush valves	Regular, Dual & I Flush advantages					
Colour:	White	Material:	Ceramic - Vitreous China					
Outlet	Vertical	BOM doc.NO.						

Internal diameter of inlet hole Ø 58 +2 -1 mm Technical Details:

External diameter of outlet hole Ø 100 +5 -2 mm

ARTICLE NAME: WALL HUNG WC





TECHNICAL DIMENSIONS 40 -205 ± 25-425 F.F.Lvl. TOP VIEW SIDE VIEW BACK VIEW

(TOLERANCE ± 5 MM) PRODUCT DIMENSIONS USP Length (mm) Width (mm) Height (mm) Net weight (kg) Box rim with heavy duty seat cover, deep sump for efficient flushing, Anti germ 355 585 410 glaze ACCESSORIES PROVIDED UF Soft Close Seat cover OPS-WHT-15103UF Inlet & Outlet gasket ZPS-WHT-GK01 ZPS-WHT-SC01 Side cap ACCESSORIES RECOMMENDED ZPS-SNS-RB01 & ZPS-MST-RB02 Rag bolt



Concealed cistern model no



JCS-WHT-2400S,2400FS,2400WS

ALL DIMENSIONS ARE IN MM.

CARE AND CLEANING GUIDELINES

- * Vitreous china sanitary ware products are fragile in nature and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and use thereafter.
- \bigstar The product is heavy and it is recommended that two persons hold it while it is being fixed.
- \bigstar Carefully inspect the new product for damage before installation.
- ★ Risk of product damage. Over tightening may cause breakage or chipping of vitreous china.
- ★ Risk of external leakage. Do not lift or rock the bowl after placement.
- * Always test your cleaning solution on an inconspicuous area on the product before applying it to the entire surface.
- ★ Do not allow cleaners to sit or soak on the product.
- ★ Use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad.
- ★ Wipe surfaces clean and rinse completely with water immediately after applying cleaners.
- 🖈 Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion.
- ★ Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth.

CERTIFICATION

Compliance: IS 2556.2:2004, IS 2556.1:1994 , EN 997 :2012+A1

All technical dimensions are in accordance to British standards, Bureau of Indian Standards												
PACKAGING DETAIL				LOADING PALLET DETAIL								
Length (mm)	Width (mm)	Height (mm)	Gross Weight(kg)	Length (mm)	Width (mm)	Height (mm)	No of pi	eces on pallet				
615	400	480	36.5	1140	1140	2285 16		16				
	JP UP											
Prepared By		Controlled By		Verified By		Approved By						
Designer		Quality control		Product Manager	uct Manager Sa		Sanitaryware Head					
Date												
Revision/Version 1				Plotter Updated on	Month	10-Jul	Year	2018				