



| | |
|--|--|
| Product code | SNR-CHR-51031 |
| Description | Sensor Faucet for Wash Basin in Rectangular Shape Deck Mounted Complete with Control Box (Battery Operated) |
| Water Supply | Cold and hot water (2 inlets) |
| Water Temperature | 5°C - 65°C |
| Inlet Water Connection | 1/2" BSP / 15mm |
| Flow Rate | 6.51 LPM @ 3 bar |
| Recommended Water Pressure | 0.5 Bar - 6.0 Bar |
| Material Composition Specification in Percentage | <p>Brass Ingots as per IS:1264-1997 Cu (58.0-63.0), Sn (0.0-1.0), Pb (0.5-2.5), Ni (0.0-1.0), Al (0.2-0.8), Mn (0.0-0.5), Total Impurity (0.0-2.0), Zn (Remainder)</p> <p>Brass Rod as per IS:319-1989 Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder)</p> |
| Solenoid Valve Specification | <p>"Operating pressure 0.5 - 6.0 bar Nominal Voltage : 6 Volt DC IP67 Protected : Very robust, reliable solenoid valve Low power consumption : Bi-stable pulse controlled"</p> |
| Electronic Parameter Setting Procedure |  IR Touch (No need of remote controlle) |
| Adjustable Parameters | <p>Detection Range : 1 - 8 level, default : 6, Follow up Time : 1 - 10 seconds, default : 1-2 Second In line purge feature : (Range - off, 12hrs ,24 hr, 48 hrs), default : off</p> |
| Power Source | 6 Volt Battery - Duracel CR-P2 Ultra Lithium 223 , 1400mAh |
| Water Tightness | 10 Bar (Pass) |
| Pressure Resistance | 25 Bar (Pass) |
| Finish | <p>"Plating: Nickel-10.0 micron Chromium-0.3 micron Salt Spray (500 hrs + Validated) Adhesion (Pass)"</p> |
| Available Color Finishing | CHROME (CHR) |
| <p>DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.</p> | |