



Product Code	KUB-CHR-35671F
Description	Kubix Thermostatic In-wall Bath and Shower Valve 20mm with Built-in Non Return Valves
Flow Rate	31.06 LPM @ 3 bar
Recommended Water Pressure	0.5 Bar - 5 Bar
Brass Specification in Percentage	<p>Brass Ingots as per IS:1264-1997 Cu (58.0-63.0), Sn (0.0-1.0), Pb (0.5-2.5), Ni (0.0-1.0), Al (0.2-0.8), Mn (0.0-0.5), Total Impurity (0.0-2.0), Zn (Remainder)</p> <p>Brass Rod as per IS:319-1989 Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder)</p> <p>Brass Sheets as per IS:410-1977 Cu (61.5-64.5), Pb (0.0-0.3), Fe (0.0-0.075), Total Impurity (0.0-0.6), Zn (Remainder)</p>
Specification	<ul style="list-style-type: none"> • Cartridges made of high performance thermostatic polymer materials that meet the global standards for high and low pressure • High technology thermoplastic polymer minimises lime-scale build up • Standard temperature range: 15° C to 60° C (59-104°F) • Shower mixer contains ceramic cartridge for divert water in two outlets. • Protected against backflow
Finish	Plating: Nickel-10.0 micron Chromium-0.3 micron Salt Spray (500 hrs + Validated)
Available Colour Finishing	CHROME (CHR)
* As per in-house testing done on automatic life cycle testing machine made by Giussain, Italy	
DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.	