

# ONS-WHT-10953BIUFSM

### SPECIFICATION DATA SHEET

#### DRODUCT DETAILS

FRODUCT DETAILS								
Manufacturer :	Jaquar	Туре:	Wall hung WC (water closet)					
Range	Ornamix	Flush valves	Regular, Dual & I Flush advantages					
Colour:	White	Material:	Ceramic - Vitreous China					
Outlet	Vertical	BOM doc.NO.						


Internal diameter of inlet hole Ø 58 +2 -1 mm Technical Details: External diameter of outlet hole Ø 100 +5 -2mm

### ARTICLE NAME: WALL HUNG WC







# TECHNICAL DIMENSIONS



TOP VIEW





USP

SIDE VIEW	BACK VIEW
OIDE VIEW	9

(TOLERANCE ± 5 MM)

Width (mm)	Height (mm)	Net weight (kg)					
70 490 36		25.00	Rimless with UF slim seat cover,Blind installation, Anti germ glaze				
ACCESSORIES PROVIDED							
UF soft close slim seat cover			ONS-WHT-10101				
Inlet & Outlet gasket			ZPS-WHT-GK01				
Fixing kit			ZPS-WHT-FB13				
ACCESSORIES RECOMMENDED							
Rag bolt			ZPS-SNS-RB07				
Concealed cistern model no			JCS-WHT-2400S,2400FS,2400WS				
	490  UF soft close Inlet & Ot Fixi Rag	490 365  UF soft close slim seat cover Inlet & Outlet gasket Fixing kit  Rag bolt	490 365 25.00  ACCESSO  UF soft close slim seat cover Inlet & Outlet gasket Fixing kit  ACCESSORIE  Rag bolt				





# **CARE AND CLEANING GUIDELINES**

- \* Vitreous china sanitary ware products are fragile in nature and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and use thereafter.
- $\bigstar$  The product is heavy and it is recommended that two persons hold it while it is being fixed.

PRODUCT DIMENSIONS

- $\bigstar$  Carefully inspect the new product for damage before installation.
- \* Risk of product damage. Over tightening may cause breakage or chipping of vitreous china.
- $\bigstar$  Risk of external leakage. Do not lift or rock the bowl after placement.
- ★ Always test your cleaning solution on an inconspicuous area on the product before applying it to the entire surface.
- $\bigstar$  Do not allow cleaners to sit or soak on the product.
- ★ Use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad.
- ★ Wipe surfaces clean and rinse completely with water immediately after applying cleaners.
- 🖈 Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion.

★ Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth.

### CERTIFICATION Compliance: IS 2556.2:2004, IS 2556.1:1994, EN 997:2012+A1/SASO 1473:2016/CE

All technical dimensions are in accordance to British standards. Bureau of Indian Standards







, an economical annication		aras, Darcaa or maian s		BIS				
	PACKAG	ING DETAIL		LOADING PALLET DETAIL				
Length (mm)	Width (mm)	Height (mm)	Gross Weight(kg)	Length (mm)	Width (mm)	Height (mm)	No of pieces on pallet	
510	430	416	27.00	1140	1140	2285	16	
	_							





J.P.							
Prepared By	Controlled By	Verified By	Approved By	у			
Designer	Quality control	Product Manager	Sanitarywa	Sanitaryware Head			
Date							
Revision/Version 1		Plotter Updated on Month	26-Aug	Year	2019		