



<b>Product Code</b>	SHA-CHR-1215F
<b>Description</b>	Exposed Shower Pipe with Provision for Simultaneous Working of Showers with Operating Diverter Knob, Flat Shape 1071X50X15mm & 350mm Wide with Sliding Holder for Hand Shower, Wall Bracket & 15mm In-wall Water Inlet Connection for Connection To In-wall Shower Mixer (without Showers)
<b>Recommended Water Pressure</b>	1.0 Bar - 3.0 Bar
<b>Material Composition Specification in Percentage</b>	<p><b>Brass Rod as per IS:319-1989</b> Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder)</p> <p><b>Brass Sheets as per IS:410-1977</b> Cu (61.5-64.5), Pb (0.0-0.3), Fe (0.0-0.075), Total Impurity (0.0-0.6), Zn (Remainder)</p> <p><b>Brass Pipe as per IS:407-1996</b> Cu (62.0-65.0), Pb (0.0-0.3), Fe (0.0-0.01), Total Impurity (0.0-0.6), Zn (Remainder)</p> <p><b>ABS Specification</b> Specific Gravity g/cm<sup>2</sup> (1.06-1.10), Melt Mass Flow Rate g/10 min. (20-26), Rockwell Hardness (95-115), DTUL @ 66 psi /0.45 MPa 0C (78-102)</p>
<b>Water Tightness</b>	5 bar (Pass)
<b>Finish</b>	Plating: Nickel-10.0 micron Chromium-0.3 micron Salt Spray (200 hrs + Validated) Adhesion (Pass)
<b>Available Colour Finishing</b>	CHROME (CHR)
<p>DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. Jaquar reserves the right to make the necessary amendments at any time without prior notice.</p>	